## SOUNDPROOF TYPE DIESEL GENSET DHY120KSE 120kVA 50Hz.



Diesel generator SOUNDPROOF type, powered by 6 cylinders 4 stroke water cooled direct injection engine with electric start, for Industrial applications, large fuel tank providing over 8 hours running, AVR for smooth voltage output, large muffler to reduce noise harmful effects, Bottom fuel tank, air preheating system for easy start up (we recommend water heater for cold weather). Two bottom holes for the forklift and two hooks on the cover top. Digital control panel, Emergency stop button, fuel intake hole outside the canopy, weather proof canopy.

ΗΥUNDΔΙ

			1		
	RATED POWER (kW/kVA)	87 / 109			
	MAX. POWER (kW/kVA)	96 / 120		MEASUREN	
	FREQUENCY (Hz)	50	Mellin are Des	GENERATOR V	
	VOLTAGE (V)	230 / 400		GENERATOR C GENERATOR FI	
	CURRENT (A)	157		POWER FACTO	
	CONTROLLER	IL-NT MRS 10		DIL PRESSURE	
GENERATOR SET	ATS PORT	INCLUDED	4	COOLANT TEM	PERATURE
	BATTERY (Ah)	2x12V-80Ah		BATTERY VOLT	AGE
	FUEL TANK CAPACITY (L)	375		ENGINE ROTAT	
	COOLING FLUID VOLUME (L)	28	6	ENGINE HOURS	S RUN
	FUEL CONSUMPTION (I/h 50/100% loading)	15.88 / 31.8		BREAKER	
	RUNNING TIME UNDER (h 50/100% loading)	23.6 / 11.8	and the second se	ИСВ (0~125A)	
	NOISE LEVEL BEHIND 7 METERS (dBA)	72	•	ACCB (125~100	00A)
	ENGINE MODEL	HY6A3L-DA		POWER OU	TPUT AREA
	POWER OUTPUT (kW/1500rpm)	113	7	ERMINALS U.	/.W.N.PE
	ROTATE SPEED	1500 RPM	WARNING High Voltage	3 X SINGLE PH	ASE SOCKETS
ENGINE	SPEED REGULATION	ELECTRIC			
	STARTING METHOD	ELECTRIC			
	DISPLACEMENT (cc)	6500			_
	OIL CAPACITY (L)	16		InteliLite <sup>NT</sup> MF	
	ALTERNATOR	274D			Mode O K O Homp Fault Stop
ALTERNATOR	RATED POWER (kW/kVA)	91 / 114			
ALIERNATOR	POWER FACTOR (Cosφ)	0.8			
	VOLTAGE REGULATION	AVR / BRUSHLESS			170
	LOW OIL PRESSURE	YES	MRS 10	MRS 10	3
ALARMS	BLOCK ON START UP	YES		MANUAL AND	
	LOW BATTERY	YES	MANUAL AND REMOTE		ROLLER WITH
	HIGH TEMPERATURE ON WATER	YES	START CONTROLLER	SUPPORT FO	R EFI ENGINES
	LOW OIL LEVEL	YES			
	LOW RUNNING ON ENGINE	YES		MRS10	MRS16
	EMERGENCY STOP	YES	PIN PASSWORD	YES	YES
	N.G. (kg.)	2020	RS232/485 INTERFACE	-	-
	G.W. (kg.)			OPTIONAL	OPTIONAL
LOGISTICAL DATA	PRODUCT DIMENSIONS (mm)	3650×1150×1920	FAULTS REPORT	NO	YES
	CAPACITY (units/container)	1/20GP;3/40GP;3/HQ	MULTI-LANGUAGE FUNCTION	YES	YES
				1E0	IE3

**RECOMMENDED SPARE PARTS** 



TURBO OIL FILTER ELEMENT

FUEL FILTER ELEMENT





**NTU** 

1

1

1

1

ATS BOX	,

-

	1	-	
WA	TER	HEAT	ER

OIL	HE.	АТ	ER	

FUEL	TANK

MODEL TYPE	QTY
ATS1-200A	1
2000W	1
300W	1
-	1
	ATS1-200A 2000W 300W

**OPTIONAL ACCESSORIES** 

\* Product might be different from pictures shown

\* specifications might vary as continuous product development

Annerman Oy www.profil.fi

ZJX0708

CX0810S